

FG-K Series

Bench & Platform Scales

**Built to last,
easy to operate
anywhere**



***High Resolution
Option Available
(Non-NTEP)**

Features

- Excellent general use bench or platform scale for shipping, receiving, checking, stock control, and much more
- Easy to set up and operate with stable, accurate, large display - plus, fully flexible internal software settings
- Compact & lightweight, AC adapter (standard) or battery operation - use it anywhere you need it, from warehouse to office
- Removable stainless steel weighing pan for easy cleaning
- Weigh Pan Dimensions:
M Models 11.8" x 15" (300 x 380 mm)
L Models 15.4" x 20.9" (390 x 530 mm)
- (KAM) with column
(KBM) without column
- Rugged heavy duty construction to take the punishment of industrial use, cleaning & transportation
- Optional RS-232C allows easy connection to a printer or computer for record keeping or system control. A current loop interface is also an available option
- Selection lb/kg via pushbutton
- Full scale pushbutton tare

NTEP Approved



Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #2015

www.andweighing.com

last saved:4/25/04



A&D
A&D WEIGHING
...Clarity is Better Value

1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

FG-K (NTEP) Series Specifications:

Model	FG-30KAM FG-30KBM	FG-60KAM FG-60KBM	FG-150KAM FG-150KBM	FG-60KAL	FG-150KAL	FG-200KAL
Capacity (kg)	30 x 0.01	60 x 0.02	150 x 0.05	60 x 0.02	150 x 0.05	200 x 0.05
Capacity (lb)	60 x 0.02	150 x 0.05	300 x 0.1	150 x 0.05	300 x 0.1	400 x 0.1
Display	7 segment LCD display (Character height 26 mm)					
Operating Temperature	-10C ~ 40C / 14F ~ 104F, less than 85% RH (no condensation)					
Weight	FG-KAM: 11.2 kg / FG-KBM: 9.7 kg			16.4 kg		
Pan Size	300 x 380mm / 11.8 x 15.0 inches			390 x 530 mm / 15.4 x 20.9 inches		
Battery Life	Approximately 150 hours with alkaline dry cell battery					

Options and Accessories:

- FG-23RS-232 C Interface
- FG-24Comparator/Set Point Relay Outputs
- FG-25Display Wall Mount Bracket
- FG-26Carrying Handle
- FV-05AC Adaptor (110 V)
- FG-08.....High Resolution Modification (Non-NTEP)

Fax-on-Demand
 (800) 726-7099, Press 2 / (408) 263-2278
 Document #2015
www.andweighing.com

last saved:4/25/04



1555 McCandless Drive
 Milpitas, CA 95035, USA
 Toll Free: (800) 726-7099
 Phone: (408) 263-5333
 Fax: (408) 263-0119