

SF & SG Series

Retail Price Computing Scales

Outstanding Price/Performance Value for all types of products in retail stores; for Fruit, Produce, Meat, Bakery, Candy, Ice Cream, Coffee, or Hardware

Push-button and
Keyboard Tare
(zero) entries

Splashproof
keyboard &
display

NTEP Approved



SF Series

SG Series

Fast, Accurate,
Legal-for-Trade

Large wide angle
displays for fast,
unmistakable
readings

User Friendly,
simple, efficient
operation

Features

- **Four Series to choose from:**

- SF-KA – Dual Display Tower Type, Vacuum Florescent Display, AC Mains
- SF-KB – Dual Display Tower Type, Liquid Crystal Display, AC Adapter or Batteries
- SF-KC – Dual Display Tower Type, Vacuum Florescent Display, AC Adapter
- SG-KA – Dual Display Table Top Type, Liquid Crystal Display, AC Adapter or Batteries

- **Three capacities within each Series:**

Select the best model & capacity to suit individual needs:

15 lb x 0.005 lb (6kg x 0.002 kg)

30 lb x 0.01 lb (15 kg x 0.005 kg)

60 lb x 0.02 lb (30 kg x 0.01 kg)

- **Large Stainless Steel Pan** – Resists damage and corrosion, easy to clean.

- **Durable** - Two (2) Year Warranty.

- **Store Weight & Prices:**

30 items for all SF Models

12 items for all SG Models

- **Transaction Accumulator** – Provide customer total for multiple items.

- **Easy to clean** – Wipe down keyboard and display

- **Optional RS-232C interface** – For printer or computer connection

Fax-on-Demand

(800) 726-7099 / (408) 263-0560, Press 2

Document #1105

www.andweighing.com



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

SF Specifications (Tower Type, Dual Display)

Model	SF-6KA / KB / KC	SF-15KA / KB / KC	SF-30KA / KB / KC
Capacity/Resolution (lb)	15 lb x 0.005 lb	30 lb x 0.01 lb	60 lb x 0.02 lb
Capacity/Resolution (kg)	6 kg x 0.002 kg	15 kg x 0.005 kg	30 kg x 0.01 kg
Non-Linearity (lb / g)	+ 0.005 lb / + 2g	+ 0.01 lb / + 5g	+ 0.02 lb / + 10g
Repeatability (lb / g)	0.005 lb / 2g	0.01 lb / 5g	0.02 lb / 10g
Display	Vacuum Florescent – SF-KA/KC		Liquid Crystal – SF-KB
Display Indications	Weight – 5 digits	Total Price – 7 digits	Unit Price – 6 digits
Pan Size (width x depth)	11.8 (W) x 11.0 (D) inches / 300(W) x 280(D) mm		
Weight (appx.)	12.1 lbs / 5.5 kg		
Power	SF-KA: AC only, SF-KB & SF-KC: AC adapter or batteries (6 “D” – not included or rechargeable battery pack – option for the SF-KC only)		
Battery Life (appx.)	300 hours w/ manganese, 500 hours w/alkaline cells		
Operating Temperature	-10°C to +40°C (14°F to 104°F), RH less than 85%		
Physical Dimensions	mm	465(W) x 425(D) x 460(H) mm	
	inches	18.3”(W) x 16.7”(D) x 18.1”(H)	
Standard Accessories	Manual (all models), AC adapter (SF-KB/KC models only)		

Note: All models are lb. only. To order metric models, add “M” to end of model # (example: SF-6KBM).

SG Specifications (Table Top Type, Dual Display)

Model	SG-6KA	SG-15KA	SG-30KA
Capacity/Resolution (lb)	15 lb x 0.005 lb	30 lb x 0.01 lb	60 lb x 0.02 lb
Capacity/Resolution (kg)	6 kg x 0.002 kg	15 kg x 0.005 kg	30 kg x 0.01 kg
Non-Linearity (lb / g)	+ 0.005 lb / + 2 g	+ 0.01 lb / + 5 g	+ 0.02 lb / + 10 g
Repeatability (lb / g)	0.005 lb / 2 g	0.01 lb / 5 g	0.02 lb / 10 g
Display	Liquid Crystal		
Display Indications	Weight – 5 digits	Total Price – 7 digits	Unit Price – 6 digits
Pan Size (width x depth)	11.8”(W) x 11.0”(D) / 300(W) x 280(D) mm		
Weight (appx.)	9.9 lbs / 4.5 kg		
Power	AC adapter or batteries (6 “D” – not included)		
Battery Life (appx.)	300 hours w/ manganese, 500 hours w/alkaline cells		
Operating Temperature	-10°C to +40°C (14°F to 104°F), RH less than 85%		
Physical Dimensions	mm	330(W) x 425(D) x 108(H) mm	
	inches	13.0”(W) x 16.7”(D) x 4.25”(H)	
Standard Accessories	Manual, AC adapter		

Note: All models are lb. only. To order metric models, add “M” to end of model # (example: SG-6KAM).

Specifications are subject to change without notice

Options for SF Series

- SF-03 Serial Interface (RS-232C)
- SF-09 NiCd Rechargeable Battery Pack (for SF-KC model only)
- SF-10 **Stainless Steel Meat/Produce Pan**
- 07:SF In-use covers for SF Series (5 ea)

Options for SG Series

- SG-03..... Serial Interface (RS-232C)
- SG-11 **Stainless Steel Meat/Produce Pan**
- 07:SG In-use covers for SG Series (5 ea)

Type Approvals:

NTEP: 99-076

Canadian: AM-5329

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1105

www.andweighing.com



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119